



DESIGN DETAILS

HYDRAULIC TEST PRESSURE : 28 bar.g.
 OIL WORKING PRESSURE : 20 bar.g.
 ELECTRICAL TESTS : LOAD - SPECIFIED ± 2.5%
 INSULATION : 40 MEGOHMS MIN.

GENERAL

FINISH : CLADDING PRIMED & PAINTED MAYFAIR BLUE
 ALL MATERIALS MILD STEEL
 DIMENSIONS IN 'mm' UNLESS OTHERWISE STATED
 DUE TO INDIVIDUAL REQUIREMENTS SOME DETAILS MAY DIFFER

HEATER TYPE	SA (m ²)	'A'	'B'	'C'	kW	'E'
CES 300	1.0	1000	273	405	6	1220
CES 400	1.3	1000	273	405	9	1220
CES 500	1.6	1000	273	405	9	1220
CES 600	1.9	1000	273	405	12	1220
CES 700	2.2	1500	356	520	18	1220
CES 800	2.6	1500	356	520	18	1220
CES 900	2.9	2000	406	580	18	1220
CES 1000	3.2	2000	406	580	18	1676
CES 1500	4.8	2000	457	640	21	1676
CES 2000	6.4	2000	457	640	21	1930

AS TITLE BLOCK

Rev F		Rev D		Rev B		A.K. WAUGH LIMITED 49 DALSETTER AVENUE, GLASGOW, G15 8TE.	DRAWN	A. Waugh	
Rev E		Rev C		Rev A	Use SS Parts with Tallow		TITLE	DATE	20.09.04
								SCALE	N/A
								DRAWING No.	CES-GEN-04
								REVISION	0 X