

DESIGN DETAILS


HYDRAULIC TEST PRESSURE : 20 bar.g.
 OIL WORKING PRESSURE : Tank Head
 ELECTRICAL TESTS : LOAD - SPECIFIED ± 2.5%
 INSULATION : 40 MEGOHMS MIN.
 xx off x kW REMOVABLE CORE HEATING ELEMENTS

GENERAL

ALL MATERIALS MILD STEEL UNLESS OTHERWISE STATED
 DIMENSIONS IN 'mm' UNLESS OTHERWISE STATED
 DUE TO INDIVIDUAL REQUIREMENTS SOME DETAILS MAY DIFFER

HEATER TYPE	KW	A	B	C	D	E
OHR 01	6	1100	220	340	150	250
OHR 02	9	1100	220	340	150	250
OHR 03	12	1100	270	405	150	250
OHR 04	18	1100	270	405	150	250
OHR 05	24	1100	320	460	150	300
OHR 06	30	1100	320	460	150	300
OHR 07	36	1200	320	460	150	300

Rev F		Rev D		Rev B	
Rev E		Rev C		Rev A	

 A.K. WAUGH LIMITED 49 DALSETTER AVENUE, GLASGOW, G15 8TE. TITLE TYPICAL LAYOUT - OUTFLOW HEATERS	DRAWN	A. WAUGH
	DATE	02/07/02
	SCALE	N/A
	DRAWING No.	OUTOEH-01
	REVISION	0

AS TITLE BLOCK